

Briton 378

Push Bar
Panic Latch

Certified to EN 1125
and UKCA & CE marked



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors up to 1300mm wide
- Site reversible - easy to hand on site
- Rim panic latch with single point latching
- Suitable for single doors and double rebated doors when used in combination with Briton 376 panic bolt and double door strike.



Briton 376

Push Bar
Panic Bolt

Certified to EN 1125
and UKCA & CE marked



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors up to 1300mm wide (extension rods required to achieve maximum height)
- Site reversible - easy to hand on site
- Two-point locking for extra security
- Anti-thrust to prevent forced latch retraction
- Adjustable top & bottom shoots
- Supplied with easy clean socket
- Suitable for single and double rebated doors when used in combination with Briton 378 panic latch and Briton 378DDS double door strike.
- Suitable for non rebated doors when used in combination with the Briton 376 Panic bolt.



Briton 377

Push Bar Panic
for Double
Rebated Doors

Certified to EN 1125
and UKCA & CE marked



For Double Rebated Doors

- Suitable for use on fire & smoke doors up to 2600mm wide (extension rods required to achieve maximum size)
- Three-point locking for extra security
- Anti-thrust device, prevents forced latch retraction
- Comprises of Briton 376 vertical panic bolt, 378 reversible rim panic latch and 378DDS double door strike in one convenient pack
- Self-handed and site reversible
- Adjustable top & bottom shoots



Briton 379.N

Push Bar Panic
with Mortice
Nightlatch

Certified to EN 1125
and UKCA & CE marked



For Single & Double Rebated Doors

- Suitable for use on fire & smoke doors up to 1300mm wide
- Supplied with dual profile cylinder mortice nightlatch, accepts both euro and oval profile cylinders (cylinder not supplied)
- Self-handed and site reversible
- Anti-thrust device to prevent forced latch retraction



Briton 1438

Push Pad
Emergency Latch

Certified to EN 179
and UKCA & CE marked



For Single & Double Rebated Doors

- Pad operated rim latch
- Suitable for use on single doors and the first opening leaf of double rebated doors when used in combination with Briton 372 vertical bolt device and double door strike.
- Site reversible for left or right hand
- Can be used with a rim cylinder fitted to the outside of the door



Briton 372

Push Pad
Emergency
Exit Bolt

Certified to EN 179
and UKCA & CE marked



For Single & Double Non Rebated Double Doors

- Suitable for use on fire & smoke doors up to 2500mm high (extension rods are required to achieve the maximum sizes)
- Two point locking for extra security - Security Grade 4: 3,000 Newtons
- Double vertical bolts - self-handed
- Anti-thrust device to prevent forced latch retention
- Adjustable top and bottom shoots
- Suitable for single and non rebated double doors when used in combination with Briton 1438 rim latch device and double door strike



Panic Exit Hardware

EN 1125

Panic applications require an operating device that covers the width of the door. Used by members of the public it must provide a safe and effective escape with minimum effort and without prior knowledge of operation.

Typical applications:

- ✓ Shops
- ✓ Schools
- ✓ Hospitals
- ✓ Theatres & Cinemas

Emergency Exit Hardware

EN 179

Emergency applications require only a single point of operation. Used in low occupancy environments, these should only be used by trained personnel and never accessed by the public or people unfamiliar with the escape drill.

Typical applications:

- ✓ Offices
- ✓ Private Flats & Apartments
- ✓ Factories
- ✓ Store/Boiler Rooms



Located in a
Public Area -
Certified to EN 1125



Located in a
Non Public Area -
Certified to EN 179



Level of security



Certifire approved



CE & UKCA Marked
to EN 1154 & EN 1155



Capable of meeting
BS8300 approved
Document M
requirements



Fire tested to
EN 1164 to achieve a
rating on timber and
metal doors



Tested to ISO 14025 and
EN 15804 environmental
product declarations

Need Access from Outside?

For single and double doors (fitted to the first opening leaf)

- Lever or knob operated version.
- Supplied with 40mm euro profile cylinder as standard (available masterkeyed or keyed alike).
- Self-handed or site reversible.



1413.LE



1413.KE

For metal doors add 'M' to the ordering code e.g. 376M or 377M

