

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

“BRITON 372 (See ANNEX A) 389 (See ANNEX B) 1438 (See ANNEX C) Push Pad Range” Emergency Exit Devices

Intended use: For use on single and double leaf escape route doors, including fire resisting/smoke control doors & locked doors on escape routes.

Essential characteristics	Performance	Harmonised technical specification
	<p>Mechanical Test Evidence : 178821 / 180257 & 182650-C/F/G/H/I/K / 363384 / 420071 / 420093 & 420136</p> <p>Fire Test Evidence : Warres 127579 / C128348 / 137635 & 140181 / 422916</p>	
<p>Clause 4.2.1 Ability to release (for doors on escape routes)</p> <p>Release function</p> <p>Push pad</p> <p>Single doorset</p> <p>Double doorset</p> <p>Exposed edges and corners</p> <p>Push pad installation</p> <p>Operating element projection</p> <p>Operating element face (Push Pad)</p> <p>Push pad operating gap</p> <p>Test rod</p> <p>Push pad release operation</p> <p>Accessible gap</p> <p>Door free movement</p> <p>Top vertical bolt</p> <p>Keepers</p> <p>Keepers dimensions</p> <p>Door mass and dimensions</p> <p>Outside access device</p> <p>Release forces</p> <p>Security requirement</p>	<p>< 1 sec</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Z < 250 mm</p> <p>W < 100mm</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Pass</p> <p>Pass – (372 Annex A Only)</p> <p>Pass</p> <p>Pass – (372 Annex A Only)</p> <p>Door mass ≤ 200 Kg, door height ≤ 2500 mm, door width ≤ 1300 mm</p> <p>Pass</p> <p>Type B < 150 N</p> <p>Grade 4</p>	<p>BS EN 179 : 2008</p>

Certificate of Constancy of Performance

2812-CPR-ABB020

<p>Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes) Corrosion resistance Temperature range</p> <p>Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance – Push Pad Abuse resistance –Vertical rod Final examination</p>	<p>Grade 3 : 96 hours Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 500 N & 1000N 500 N – (372 Annex A Only) Type B < 150 N</p>	<p>BS EN 179 : 2008</p>
<p>Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes) Re-engagement force</p>	<p>< 50 N</p>	
<p>Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes) Durability Re-engagement force</p>	<p>Grade 7: 200 000 cycles < 50 N</p>	
<p>Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes) Suitability of panic exit devices for use on fire resisting doorsets assemblies –</p> <p>Additional requirements</p>	<p>Grade B: Suitable for use on fire/smoke door assemblies.</p>	
<p>Clause 4.1.25 Control of Dangerous substances</p>	<p>If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.</p>	

Certificate of Constancy of Performance

2812-CPR-ABB020

Briton Product	Single Door (Standard Keeper)	Double Door (Standard Keepers)	Approved with Alternate Strike or Keeper			
			378 DDS	376 MDS	378 MDS	379 MDS
ANNEX A						
372	✓	✓	-----	✓	-----	-----
372M	✓	✓	-----	✓	-----	-----
372OEM	✓	✓	-----	✓	-----	-----
372.P	✓	✓	-----	✓	-----	-----
372M.P	✓	✓	-----	✓	-----	-----
372OEM.P	✓	✓	-----	✓	-----	-----
ANNEX B						
389.N	✓	✓	-----	-----	-----	✓
389M.N	✓	✓	-----	-----	-----	✓
389OEM.N	✓	✓	-----	-----	-----	✓
ANNEX C						
1438	✓	✓	✓	-----	✓	-----
1438M	✓	✓	✓	-----	✓	-----
1438OEM	✓	✓	✓	-----	✓	-----
Accessories						
Model Number	Description					
Briton 1413.LE	Lever outside access device (Suitable for use with all devices)					
Briton 1413.KE	Knob outside access device (Suitable for use with all devices)					
Briton 1413.BP	Retrofit Plate (Suitable for use with all devices)					
Briton 9260 Codelock	Lever outside access device (Suitable for use with 372 & 1438 range only)					
P816 & 816 Rim Cylinder	Rim cylinder for use 1438 products only					

Certificate of Constancy of Performance

2812-CPR-ABB020

Placed on the Market under the name of:

Allegion (UK) Ltd
35 Rocky Lane, Birmingham,
West Midlands, B6 5RQ

and produced in the manufacturing plant

V/010

This is coded form and the information is held by the Notified Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

BS EN 179: 2008

Under System 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 26/10/2020 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the notified product certification body.

Valid to: **24/10/2020**

ERO Project Reference: **EROWF10008**



Paul Duggan
Certification Manager

