Briton Overhead Closers



3934 - Electromagnetic Hold-open or Swing-free (Level 5)



Smart, reliable and fire safe

Features & Benefits

- Template adjustable power Size EN 3-4 (see table)
- Stainless steel grade 304 softline cover available in silver and satin steel finishes to suite with Briton 2300 and 2700 closers with softline covers to complement a variety of door hardware ranges.
- Designed for use on low voltage circuits 24V DC linked to a fire alarm
- Solution offering hold-open and free swing
- Easy Installation
- Attractive compact design
- Test switch simulates fire condition of check operation
- When the fire alarm is activated, the door will close automatically from any position to help prevent the spread of fire

Mounting	Power size	Max. door opening	EN Classification
Door mounted	3	180°	3 8 3-4 1 1 3
	4	110°	
Transport and the d	3	180°	3 8 3-4 1 1 3
Transom mounted	4	110°	
Parallel mounted	3	170°	383113

Product Ref:	Description	Mounting Option	Finishes
3934	Electromagnetic hold-open/swing-free closer - Template adjustable EN 3-4	Regular and Transom mount	SSS

Testing & Certification

CE marked to EN1154 - AE5012

CE marked to EN1155 for electromagnetic hold-open variants Fire tested to EN1634 on timber doors to achieve a 2 hour fire rating. Certifire Approved CF5598

Full Declaration of Performance available from our website at:

www.doorhardware-online.co.uk

What's in the box?

- Closer Body
- **Body Cover**
- Appropriate Arm and Bracket
- Armoured Loop
- Fixing Pack
- Installation Instructions













48 doorhardware-online.co.uk