

Briton

4700 Series

Flush bolts

A range of manually operated flush bolts for use on equal or unequal pairs of doors to keep the inactive leaf locked.



Description:	Flush bolts - open type	
Ref:	Size	End Type
4735.R.20.202	202mm x 20mm	Radiused
4735.R.20.300	300mm x 20mm	Radiused
4735.R.20.450	450mm x 20mm	Radiused
4735.R.20.600	600mm x 20mm	Radiused
4735.R.20.914	914mm x 20mm	Radiused
4735.S.20.202	202mm x 20mm	Square
4735.S.20.300	300mm x 20mm	Square
4735.S.20.450	450mm x 20mm	Square
4735.S.20.600	600mm x 20mm	Square
4735.S.20.914	914mm x 20mm	Square



Description:	Flush bolts - Fully enclosed	
Ref:	Size	End Type
4739.R.18.225	225mm x 18mm	Radiused
4739.S.18.225	225mm x 18mm	Square

Certification

- Tested to EN 12051:1999
- Graded 4 3 - 0 1 3 1
- DoP available at www.britoninspec.co.uk

Features & Functions

- Available in a range of lengths up to 914mm for use on tall doors
- Square or radiused end versions
- Stainless steel lever action bolt
- Fully enclosed option particularly suitable for timber doors
- Supplied with stainless steel fixings
- Optional floor sockets available (see below)



Ref:	Description
4736	Plunger type dust excluding floor socket for use with flush bolts - concealed fixing
4737	Easy clean floor socket for use with flush bolts - face fixing.